



TruVision 11/31 Series IP Camera Firmware V5.2 FP12 Release Notes

P/N 1073128 • REV B • ISS 5JAN17

Introduction

This is the TruVision 11/31 Series IP Camera Firmware V5.2 Release Notes with additional information not covered in the user manual. For the latest information on the TruVision 11/31 Series, please visit:

Americas: <http://www.interlogix.com/videoupgrades>

EMEA: www.utcssecurityproducts.eu

Australia: www.interlogix.com.au

Supported camera list

IP mini bullet camera:

- TVB-1101 (1.3MPX Bullet, 6 mm lens, PAL)
- TVB-3101 (1.3MPX Bullet, 6 mm lens, NTSC)
- TVB-1102 (3MPX Bullet, 6 mm lens, PAL)
- TVB-3102 (3MPX Bullet, 6 mm lens, NTSC)
- TVB-1103 (1.3MPX Bullet, 4 mm lens, PAL)
- TVB-3103 (1.3MPX Bullet, 4 mm lens, NTSC)

IP VF bullet camera:

- TVB-1104 (1.3MPX Bullet, 2.8 to 12 mm VF Lens, PAL)
- TVB-3104 (1.3MPX Bullet, 2.8 to 12 mm VF Lens, NTSC)
- TVB-1105 (3MPX Bullet, 2.8 to 12 mm VF Lens, PAL)
- TVB-3105 (3MPX Bullet, 2.8 to 12 mm VF Lens, NTSC)

IP mini dome camera:

- TVD-1101 (1.3MPX Plastic Mini Dome, PoE, PAL)
- TVD-3101 (1.3MPX Plastic Mini Dome, PoE, NTSC)
- TVD-1102 (3MPX Plastic Mini Dome, PoE, PAL)
- TVD-3102 (3MPX Plastic Mini Dome, PoE, NTSC)
- TVD-1105 (1.3MPX IP IR Outdoor Mini Dome, PoE/12 VDC, PAL)
- TVD-3105 (1.3MPX IP IR Outdoor Mini Dome, PoE/12 VDC, NTSC)
- TVD-1106 (3MPX IP IR Outdoor Mini Dome, PoE/12 VDC, PAL)
- TVD-3106 (3MPX IP IR Outdoor Mini Dome, PoE/12 VDC, NTSC)

IP VF mini dome camera:

- TVD-1103 (1.3MPX VF Mini Dome, PAL)
- TVD-3103 (1.3MPX VF Mini Dome, NTSC)
- TVD-1104 (3MPX VF Mini Dome, PAL)
- TVD-3104 (3MPX VF Mini Dome, NTSC)

IP wedge camera:

- TVW-1101 (1.3MPX Wedge, 2.8 mm lens, Grey, PAL)
- TVW-3101 (1.3MPX Wedge, 2.8 mm lens, Grey, NTSC)
- TVW-1102 (3MPX Wedge, 2.8 mm lens, Grey, PAL)
- TVW-3102 (3MPX Wedge, 2.8 mm lens, Grey, NTSC)
- TVW-1117 (1.3MPX Wedge, 2 mm lens, Grey, PAL)
- TVW-3117 (1.3MPX Wedge, 2 mm lens, Grey, NTSC)
- TVW-1118 (1.3MPX Wedge, 2.8 mm lens, White, PAL)
- TVW-3118 (1.3MPX Wedge, 2.8 mm lens, White, NTSC)
- TVW-1119 (1.3MPX Wedge, 2.8 mm lens, Black, PAL)
- TVW-3119 (1.3MPX Wedge, 2.8 mm lens, Black, NTSC)

IP wireless wedge camera:

- TVW-1103 (1.3MPX wireless, 2.8 mm lens, Grey, PAL)
- TVW-3103 (1.3MPX wireless, 2.8 mm lens, Grey, NTSC)
- TVW-1104 (1.3MPX wireless, 2.8 mm lens, White, PAL)
- TVW-3104 (1.3MPX wireless, 2.8 mm lens, White, NTSC)
- TVW-1105 (3MPX wireless, 2.8 mm lens, Grey, PAL)
- TVW-3105 (3MPX wireless, 2.8 mm lens, Grey, NTSC)
- TVW-1106 (3MPX wireless, 2.8 mm lens, White, PAL)

- TVW-3106 (3MPX wireless, 2.8 mm lens, White, NTSC)
- TVW-1116 (3MPX wireless, 6 mm lens, White, PAL)
- TVW-3116 (3MPX wireless, 6 mm lens, White, NTSC)

Improvements with Firmware V5.2 FP12

1. Included 4CIF to Main Stream resolution options.
2. Added *Delete all certificates* button to the HTTPS configuration page to purge any previously-updated certificates.
3. Added a *Disable WiFi* option on the WiFi configuration page to turn off the wireless functionality completely. All other features will be unaffected.
4. Added a *Host Name Configuration* section to the TCP/IP configuration page so that the user may register the camera name with an available DNS server to enable access based upon camera name in lieu of IP address via the browser.

Contacting Support

For help installing, operating, maintaining, and troubleshooting this product, refer to this document and any other documentation provided. If you still have questions, contact us during business hours (Monday through Friday, excluding holidays).

Note: Please be ready at the equipment before calling.

Table 1: Technical support

North America

T +1 855.286.8889

E techsupport@interlogix.com

W www.interlogix.com/customer-support

Europe, Middle East, and Africa

W Select *Contact Us* at www.utcssecurityproducts.eu

Australia

E security.tech.support@interlogix.com.au
