## TruVision® HD-Hybrid Comparison Table



		DVR 12CHD	DVR 12HD	DVR 44HD
			- 0 / 11	
Channels & Performance	Analog channels	4	8/16	8/16
	Maximum IP channels	2	4/8	8/16
	Real-time recording	HD 720p	HD 720p	Full HD 1080p
	Full HD 1080p resolution	15 fps	15 fps	30 fps
	Audio channels	4	8/16	16
Network & Streaming	Gigabit ethernet ports	1	1	1
	ezDDNS	•	•	•
	Maximum outgoing video streams	128	128	128
	Maximum in/out combined bandwidth			
	Maximum in/out combined bandwidth	60 Mbps	96/128 Mbps	200 Mbps
Storage	Max storage (TB)	2	8	16
	SATA interfaces	1	2	4
	HDD redundancy	_	•	•
	Front side accessible HDDs	_	_	•
	Expandable internal storage	_	_	•
	eSATA support	_	_	•
	NAS support	_	_	•
	Dual stream recording	_	_	•
	Auto archive	_	_	•
General Local Viewing Features & Controls	Front panel controls	•	•	•
	Browser interface	•	•	•
	HDMI	•	•	•
	VGA	•	•	•
	BNC output	•	•	•
	Bidirectional audio	•	•	•
	Alarm input/output	4/1	4/1	16/4
	Keypad support	TVK-800	TVK-800	TVK-800
	USB slots	2	2	3
	Analytics on analog channels	_	_	•
	Text insertion	•	•	•
	CD/DVD burner	Via USB	Via USB	Via USB
	Reverse playback	•	•	•
	Size	1U	1.5U	1.5U
	Rack mountable	_	•	•
Software Support	TruVision Navigator	•	•	•
	TVRmobile	•	•	•
	Advisor	•	•	•
	OnGuard <sup>®</sup>	•	•	•
	TruPortal™	•	•	•



Specifications subject to change without notice.

© 2015 United Technologies Corporation.
All rights reserved.
All trademarks are the property of their respective owners.
Interlogix is part of UTC Building & Industrial Systems,
a unit of United Technologies Corporation.