

### www.GESecurity.com

# **KTD-138** Auxiliary Function Receiver

## **Overview**

The KTD-138 is a small, economical indoor receiver that controls auxiliary functions in a Digiplex® system. It contains four double-pole relays that can be used to carry out various functions such as operating doors, turning on lamps, or switching balanced audio to a single bus line. The wall-mountable unit is packaged in a small aluminum case that features slotted mounting tabs for easy installation. All relays and ICs are socketed for easy removal and replacement.

#### **Outstanding Features**

The KTD-138 is controlled through twisted-pair cable from one or more remote Digiplex keypads. All wiring connections are made on a removable terminal strip.

Note: The KTD-138 must be programmed at the factory for specific key-to-relay assignment. To expedite processing, please contact GE Security before submitting orders for receivers in this category.



## **Standard Features**

- Low-cost receiver
- Four 1-A double-pole relays
- Removable terminal strip
- Small, easy-to-mount case



Auxiliary Function Receiver

## **Specifications**

#### Electrical

- Input voltage: 9 VAC/12 VDC, 50 to 60 Hz
- Input power: 5.5 VA
- Input data signal: RS422
- Function relays type: DPDT dry contact
- Function relays contact rating: 1.0 A @ 30 VDC

#### **Function Relays**

. Four normally open double-pole dry contact relays switchable to a common output. See figure below.

#### **Controls**

• Site select: Multiposition DIP switch

## **Connections**

• 16-position removable terminal strip

## Mechanical

- Weight: 6.4 oz (181 g)
- Material: 0.050 in (1.27 mm) aluminum
- Finish: Black anodized



**Ordering Information** 



www.GESecurity.com

As a company of innovation, GE Security reserves the right to change product specifications without notice. For the latest product specifications, visit GE Security online at www.GESecurity.com or contact your GE Security sales representative IPS-KTD-138-2004-06-15 18:53:18 [NOT RELEASED]