

# 1015 recessed magnetic contact

recessed press fit magnetic contact with wire leads  
1/4 in. dia.

The 1015 magnetic contact is designed with a flat side on the surface of the contact, which allows a flush fit on narrow surfaces.

This contact is recommended for use with casement windows, awning windows, and other areas where the contact must recess and fit into a narrow surface. It installs quickly in a 1/4-inch diameter hole. Small fins on the housing of the magnet and switch eliminate the need for glue.



## Specifications

|                           |   |
|---------------------------|---|
| Voltage:                  | 100 VAC/VDC max.  |
| Current:                  | 0.5 A max.  |
| Power:                    | 7.5 W max.  |
| Loop type:                | Closed  |
| Electrical configuration: | Normally open   |
| Gap distance:             | Up to 3/8 in.   |
| Lead type:                | 1 ft. #22 wire  |
| Dimensions:               | 1.625 in. L x 0.25 in. dia. (33 x 6.4 mm) with a 3/8 in. dia. (9.5 mm) tapered head |
| Housing:                  | Flame retardant ABS plastic   |
| Color:                    | White   |
| Regulatory:               | UL, CUL   |

- Press fit design makes installation easy—no screws or glue needed
- Attractive, added security of recessed mounting
- Flat-sided head for use in limited spaces
- 1/4-inch diameter

## Ordering information

|             |  |
|-------------|--|
| 1015N-10PKG | Recessed contact with wire leads, 1/4 in. dia., 3/8 in. gap size, white, pk/10 |
|-------------|--|

