



# Wireless Personal Panic Device

Water-resistant

## OVERVIEW

The Wireless Personal Panic Device from Interlogix features an updated design that is both chlorine- and UV-resistant for long-lasting and reliable performance. In addition, the Panic Button is water-resistant and functions as a wireless device used for activating police, fire or auxiliary alarms throughout the premises. When the panic button is pressed, the LEDs on either side of the button will blink and an alarm signal is transmitted.

The status of the battery is sent in every transmission, and the battery is field-replaceable. The panic device comes configured as a wristband, but can easily be configured as a pendant (accessories included).

## Specifications

Compatibility	Interlogix Learn Mode panels and receivers
Power Supply	3.0V lithium battery (CR1632)
Recommended Battery	Panasonic CR1632
Estimated Battery Life (at 20°C)	>5 years
Typical Standby Current	1µA
Supervisory Interval	Less than 64 minutes
Frequency	319.5 MHz
Transmitting Range	>= 500 ft open-air
Transmitter Technology	Crystal
Operating Temperature	32°F~120°F (0°C~49°C)
Storage Temperature	-30°F~140°F (-34°C~60°C)
Relative Humidity	5%~90% (non-condensing)
Enclosure	Compliant to IP68
Standard Listings	FCC, IC
Dimensions (LxWxD)	1.6 x 1.4 x .4 in. (without adaptors or wristband)
Wristband Construction	Medical grade polymer

## STANDARD FEATURES

- Activates police, fire or auxiliary alarms
- Works with all 319.5 MHz Learn Mode panels
- Water-resistant rating to IP68
- May be configured as a pendant

## Ordering Information

<b>TX-4200-01-1</b>	Wireless Personal Panic Device, White
<b>TX-4200-01-2</b>	Wireless Personal Panic Device, Black

## Accessories

<b>600-1068-1</b>	Replacement Accessories - Pendant Loop & Plug, Lanyard, Actuator Seal, Clasp, Wristbands, Base and Cover, White, 5-Pack
<b>600-1068-3</b>	Replacement Accessories - Pendant Loop & Plug, Lanyard, Actuator Seal, Clasp, Wristbands, Base and Cover, Black, 5-Pack
<b>600-1069</b>	3V Coin Lithium Battery, 5-Pack

**North America**  
T 855-286-8889

**Latin America**  
T 561-998-6114



interlogix.com

Specifications subject to change without notice.

© 2014 United Technologies Corporation.  
All rights reserved.

Interlogix is part of UTC Building & Industrial Systems,  
a unit of United Technologies Corporation.

403-3801 2014/03 (74675)