



NVR 21

8/16 IP Channel Network Video Recorder





①



SMART BANDWIDTH















OVERVIEW

The TruVision® NVR 21 (TVN 21) is a high-performance network video recorder designed to support video streams from IP video cameras. With a total of 40/80 Mbps of total bandwidth available. the TVN 21 can support up to 16 cameras at HD resolution in real-time (30fps) and many other configurations.* Flexible bandwidth allocation per channel allows users to maximize recording performance. In addition to browser, software and mobile device management tools, the NVR 21's familiar front panel controls allow for easy operation.

IP camera support includes resolutions ranging from standard VGA to 5.0 megapixel, including Interlogix and third-party IP camera manufacturers.** The NVR 21 also supports TruVision encoders for integrating existing analog cameras. Up to four internal hard disk drives may be configured for a total internal hard drive capacity of 2TB-8TB, making the TVN 21 ideal for extended storage or megapixel camera applications.

Recording options include continuous, motion, and alarm or combined scheduled recording modes. Motion recording utilizes an IP camera's built-in motion detection events, and alarms can be triggered from any of the 16 on-board alarm inputs or from alarm inputs that reside on the IP camera.

Software connectivity allows remote access to the recorder's full capabilities via Web browser or TruVision Navigator. TruVision Mobile also allows for remote device access. Configuration is quick and easy through startup wizards, IP device auto-discovery tools and ezDDNS service.

STANDARD FFATURES

Camera Support

- Up to 8/16 HD cameras (OnVIF/PSIA) in real time (30fps)
- TruVision and UltraView IP cameras from VGA through 5.0 megapixel (indoor and outdoor)
- H.264 Axis, Arecont, ACTi, Panasonic, Samsung, Sony and Vivotek (VGA/Megapixel)
- TruVision 4-, 8- and 16-channel encoders
- PTZ and dome camera control via mouse, front panel joystick and IR remote control

Recording Capabilities

- Continuous, motion or scheduled recording modes
- Event recording based upon native IP camera activity detection or via unit alarm input
- Video is stored in the native IP camera format
- Audio recording with capable IP cameras
- Redundant camera recording or independent storage groups for different durations
- Reverse playback
- Digital zoom on live and recorded video
- Text insertion via ProBridge for ATM/POS
- Watermarking for legal video authentication

Hardware

- Compact rack mountable 1.5 RU
- Up to 8TB of plug-and-play internal, front accessible hard disk storage
- Support for external hard drive (eSATA)
- 16 on-board alarm inputs and 4 configurable alarm outputs
- Local USB archiving
- Composite, VGA and HDMI output for high-quality local viewing

^{*}Reference table on page 2.


^{**}Support from third-party IP cameras may vary.

8/16 IP Channel Network Video Recorder

Specifications

Model		TVN-2108	TVN-2116	
Video/	IP Video Input	8-ch	16-ch	
Audio Input	Bi-directional Audio	1-ch, RCA (2.0 Vp-p, 1kΩ)		
Video/ Audio Output	Recording Resolution	5MP /3MP /1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF / CIF /QCIF		
	CVBS Output	1-ch, BNC (1.0 Vp-p, 75 Ω) Resolution: 704 × 576 (PAL); 704 × 480 (NTSC)		
	HDMI Output	1-ch, resolution: 1920 × 1080P /60Hz, 1920×1080P /50Hz, 1600 × 1200/60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz		
	VGA Output	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz		
	Audio Output	2-ch, RCA (Linear, 600Ω)		
	Playback Resolution	5MP /3MP /1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF / CIF /QCIF		
	Synchronous Playback	8-ch	16-ch	
Hard Disk	SATA	4 SATA interfaces		
	eSATA	1 eSATA interface		
	Capacity	2TB capacity for each HDD		
External	Network Interface	2 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interface		
Interface	Serial Interface	1 RS-232 interface (for parameters configuration, maintenance transparent channel); 1 RS-485 interface (reserved)		
	USB Interface	3 x USB 2.0		
	Alarm Interface	16 Alarm In, 4 Alarm Out		
General	Power Supply	100 ~ 240 VAC, 6.3 A, 50 ~ 60 Hz		
	Consumption (without hard disk or DVD-R/W)	≤ 45 W		
	Working Temperature	-10° C ~+55° C (14° F~131° F)		
	Working Humidity	10% ~ 90%		
	Chassis	19-inch rack-mounted 1.5U chassis		
	Dimensions (W x D x H)	17.40 × 14.61 × 2.91 in. (442 × 371 × 74mm)		
	Weight (without hard disk or DVD-R/W)	≤ 8 Kg (17.64 lb)		

Dimensional Diagram



Typical camera capacity configurations 8 Channels

Recording	Recording	Maximum Number of	Recommended Days of Storage		
Resolution Frame Rate	Interlogix IP Cameras	10 Days	20 Days	30 Days	
4CIF	15 fps	8	2TB	2TB	4TB
4CIF	25/30 fps	8	2TB	4TB	6TB
1.3 Mpx	10 fps	8	2TB	4TB	4TB
1.3 Mpx	16 fps	8	2TB	4TB	6TB
1.3 Mpx	25/30 fps	6	6TB		
2 Mpx	4 fps	8	2TB	4TB	6TB
2 Mpx	10 fps	8	4TB	8TB	
2 Mpx	25/30 fps	4	8TB		
3 Мрх	4 fps	8	4TB	8TB	
3 Мрх	12 fps	4	8TB		
5 Mpx	4 fps	7	6TB		
5 Mpx	6 fps	5	8TB		

Note: This is an indication only; results depend on cameras used and environment.

Typical camera capacity configurations 16 Channels

Recording	Recording	Recording Maximum Number of		Recommended Days of Storage		
Resolution	Frame Rate Interlogix IP Cameras	10 Days	20 Days	30 Days		
4CIF	15 fps	16	2TB	4TB	6TB	
4CIF	25/30 fps	16	4TB	8TB		
1.3 Mpx	10 fps	16	4TB	6TB	8TB	
1.3 Mpx	16 fps	16	4TB	8TB		
1.3 Mpx	25/30 fps	10	8TB			
2 Mpx	4 fps	16	4TB	8TB		
2 Mpx	10 fps	16	8TB			
2 Mpx	25/30 fps	8	8TB			
3 Мрх	4 fps	16	8TB			
3 Мрх	12 fps	10	8TB			
5 Mpx	4 fps	12	8TB			
5 Mpx	6 fps	10	8TB			

Note: This is an indication only; results depend on cameras used and environment.

Ordering Information

TVN-2108-2T	TruVision NVR 21, 8 channels, 2TB Storage
TVN-2108-4T	TruVision NVR 21, 8 channels, 4TB Storage
TVN-2108-8T	TruVision NVR 21, 8 channels, 8TB Storage
TVN-2116-2T	TruVision NVR 21, 16 channels, 2TB Storage
TVN-2116-4T	TruVision NVR 21, 16 channels, 4TB Storage
TVN-2116-8T	TruVision NVR 21, 16 channels, 8TB Storage



interlogix.com

Specifications subject to change without notice.

© 2013 Interlogix. All rights reserved. Interlogix is part of UTC Climate, Controls & Security, a unit of United Technologies Corporation.