NetworX "Operator" Telephone Interface Module

OVERVIEW

The NetworX "Operator" Telephone Interface Module is a microcomputer controlled telephone interface module that may be added to NetworX control panels. The "Operator" converts any touchtone telephone to a system keypad and allows system functions to be accessed via telephone on premise or off-site. There are 48 separate zone descriptions that may be programmed to fit the owner's needs. Each zone/output description is programmable using the 182-word library list.

Specifications

Operating power	
nominal	12VDC supplied by control panel
Current	Standby 55mA Active 130mA
Control outputs	32 X10 outputs with programmable descriptions
Dimensions (W x L x H)	3.5 x 6.0 x 1.0 in.
Telephone requirement	Touchtone telephones only
Regulatory	FCC part 15, Class B verification requirements, and FCC Part 68 Modification
	FCC Registration Number: GCQUSA-30138-AL-E

STANDARD FEATURES

- Converts any touchtone telephone to a system keypad
- Allows system functions to be accessed via telephone on or off-site
- Each zone/output description is programmable using the 182 word library list
- Compatible with the NX-6, NX-8 and NX-8E control panels

Ordering Information

NX-540E "Operator" Telephone Interface Module



interlogix.com

Specifications subject to change without notice.

© 2014 United Technologies Corporation. All rights reserved. Interlogix is part of UTC Building & Industrial Systems, a unit of United Technologies Corporation.

306-3677 2014/03 (75051)

North America T 855-286-8889

Latin America T 561-998-6114