NetworX Touch Screen Keypad



OVERVIEW

Ideal for almost any size application, the NetworX Touch Screen Keypad offers powerful yet simple control of any NetworX security system. An intuitive interface, 3.5" touch screen and Quick Keys for rapid system arming and status updates enable quick and easy system management.

Users can record their own names for different system components and leave voice messages for others when arming or disarming. When a NetworX proximity card reader (NX-1700E) is installed, users can easily manage access cards and authority levels from the convenience of the keypad.

STANDARD FEATURES

- NetworX system compatibility
- 3.5" color touch screen
- Icon-based graphic interface
- Quick Arm, Stay and Status keys
- Custom text naming for user names, areas, zones, outputs and rooms
- Access card management (when card reader NX-1700E is installed)
- Built-in message board
- 192-zone capability
- Support for up to 99 users, 8 partitions and 16 outputs
- Customizable chime groups for specific zones
- Streamlined, modern design

 North America
 Latin America

 T 855-286-8889
 T 561-998-6114

NetworX Touch Screen Keypad

Specifications

General

General	
Compatibility	Interlogix™ NetworX control panels (NX-4, NX-6, NX-8, NX-8E)
User Interface	Intuitive graphical interactive encased in a 3.5" color TFT LCD screen
Language	English
Electrical	
Operating Voltage	12VDC Regulated, supplied from control panel
Current	110mA nominal, 140mA max
Wiring	NetworX 3-wire data/communication bus
Environmental	
Operating temperature	32°F~122°F (0°C~50°C)
Physical	
Dimensions (WxHxD)	3.2 x 4.9 x 0.7 in. (82 x 125 x 18mm)
Color	Opal White with silver frame

Ordering Information

NX-1820E

NetworX Touch Screen Keypad



interlogix.com

Specifications subject to change without notice.

© 2014 United Technologies Corporation. All rights reserved. Interlogix is part of UTC Building & Industrial Systems, a unit of United Technologies Corporation.

405-3821 2014/09 (78565)